



MATERIAL SAFETY DATA SHEET

----- I. PRODUCT IDENTIFICATION -----

TRADE NAME (as labeled): LATICRETE® 9235 Waterproof Membrane

CHEMICAL FAMILY: Styrene Copolymer Latex

MANUFACTURER'S NAME: MYK LATICRETE INDAI PVT. LTD. Reviewed & Approved by
6-3-569/2, 1st Floor Kamdhenu Complex T.V. Narasimham
Rockdale compound, Somajiguda, Hyderabad Sr. Manager – R&D
Tel: +91 40 30413100 (30 lines)

----- II. HAZARDOUS INGREDIENTS -----

| CHEMICAL NAMES | CAS NUMBERS | PERCENT | ACGIH TLV | OSHA PEL | OTHER (SPECIFY) |
|-----------------|-------------|---------|-----------------|----------|--------------------|
| Ethylene Glycol | 107-21-1 | 1.5 | 5 ppm (ceiling) | N/A | N/A |
| Formaldehyde | 50-00-0 | 0.03 | N/A | N/A | N/A |

N/A = Not applicable or available

----- III. HEALTH HAZARD INFORMATION -----

SYMPTOMS OF OVEREXPOSURE for each potential route of exposure. (Possible Longer Term Effects) None known.

SIGNS AND SYMPTOMS OF EXPOSURE (Acute effects)

Inhaled: No problem normally anticipated

Contact with skin or eyes: This product may be an eye irritant. It may cause skin irritation upon prolonged or repeated contact.

Absorbed through skin: Skin absorption is unlikely.

Swallowed: Single dose oral toxicity is believed to be low.

SUSPECTED CANCER AGENT?

x NO: This product's ingredients are not found in the lists below.

YES: _____ Federal OSHA _____ NTP _____ IARC

----- IV. FIRST AID: EMERGENCY PROCEDURES -----

Eye Contact: Hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

Skin Contact: Wash off in flowing water or shower.

Inhaled: No adverse effects anticipated.

Swallowed No adverse effects anticipated by this route of exposure incidental to proper industrial handling.

----- V. FIRE AND EXPLOSION -----

Flash Point method): Non-flammable

Auto ignition temperature, °F: N/A

Flammable limits in air, volume %: Lower (LEL)_____ Upper (UEL)

Fire extinguishing materials:

x water spray

x carbon dioxide

other:

x foam

x dry chemical

Special fire fighting procedures: N/A

Unusual fire and explosion hazards: Closed containers exposed to extreme heat may rupture due to pressure buildup.

----- VI. SPILL, LEAK, AND DISPOSAL PROCEDURES -----

Spill response procedures (include employee protection measures): Small amounts of spilled material may be absorbed onto and appropriate absorbent. Prevent spilled liquid from entering sewers, storm drains, and natural waterways. Wear safety glasses and impervious gloves.

Preparing wastes for disposal (container types, neutralization, etc.): Place contaminated absorbed material into metal containers and seal.

NOTE: Dispose of all wastes in accordance with federal, state and local regulations.

----- VII. Handling and Storage -----

Store in area between 40°F and 100°F.

----- VIII. Exposure Controls and Personal Protection -----

Ventilation and engineering controls: Good general ventilation should be sufficient for most conditions

Respiratory protection (type): Not needed for most conditions

Eye protection (type): Use chemical goggles or safety glasses

Gloves (specify material): Impervious gloves, vinyl or rubber

Other clothing and equipment: Wear clean, long-sleeved bond-covering clothing

Work practices, hygienic practices: Maintain good housekeeping standards

Other handling and storage requirements: Should store at temperatures between 40 - 100°F

Protective measures during maintenance of contaminated equipment:

-----XVI Other Information-----

This information is furnished without warranty, representation, inducement or license of any kind; except that it is accurate to the best of our knowledge, or obtained from sources believed by us to be accurate.