



MATERIAL SAFETY DATA SHEET

1.PRODUCT IDENTIFICATION

TRADE NAME (as labeled): LATICRETE LIQUID # 73
CHEMICAL FAMILY:

MANUFACTURER'S NAME: MYK LATICRETE INDIA PVT.LTD
6-3-569/2, 1ST FLOOR, KAMDENU COMPLEX,
ROCKDALE COMPOUND,Somajiguda, Hyderabad – 500082
Tel: 30413100 (30 Lines)

Reviewed & Approved By:
T.V.Narasimham
Sr.Manager – R&D

II.HAZARDOUS INGREDIENTS

| CHEMICAL NAMES | CAS NUMBERS | PERCENT | ACGIH TLV | OSHA PEL | OTHER (SPECIFY) |
|----------------|-------------|---------|-----------|----------|-----------------|
| N/A | | | | | |

N/A = Not applicable or available

III.PHYSICAL PROPERTIES

| | |
|---|--|
| Vapor density (air = 1) : 624 | Melting point or range, F: N/A |
| Specific gravity: 1.000 | Boiling point or range, F: 212 F |
| Solubility in water: Emulsion | Evaporation rate (butyl acetate =1): N/A |
| Vapor pressure, mmHg at 20 C: 17.5 mm | ph: 10.0 \pm .5 |
| Appearance and odor: White, thick liquid. Slight odor. | % Volatile by weights:84% |

HOW TO DETECT THIS SUBSTANCE: (warning properties of substance as a gas, vapor, dust, or mist): N/A

This information is furnished without warranty, representation, inducement or license of any kind: except that it is accurate to the best of our knowledge or obtained from sources believed by us to be accurate.

LATEX CRETE # 73

IV. FIRE AND EXPLOSION

Flash Point, F(give method): Non-flammable or combustible in liquid form.

Auto ignition temperature, F : N/A

Flammable limits in air, volume % N/A Lower (LEL) _____ Upper (UEL)

Fire extinguishing materials:

water spray carbon dioxide _____ other: (dried resin only)
 foam dry chemical

Special fire fighting procedures : As latex, material is not combustible: However, the dried polymer is Flammable similar to wood. Burning dry polymer emits dense, black smoke.

Unusal fire and explosion hazards: N/A

V. HEALTH HAZARD INFORMATION

SYMPTOMS OF OVEREXPOSURE for each potential route of exposure.

Inhaled: No adverse effects are anticipated from inhalation.

Contact with skin or eyes: Short exposure not likely to cause significant skin irritation. Eye contact may cause slight, temporary eye irritation.

Absorbed through skin: Skin absorption is unlikely due to physical properties.

Swallowed: Single dose oral toxicity is believed to be low. No hazards anticipated from ingestion .
Exposure incidentat to industrial exposure

HEALTH EFFECTS OR RISKS FROM EXPOSURE.Ezplain in lay terms . Attach extra page if more space is needed:

Acute: N/A

Chronic: N/A

FIRST AID: EMERGENCY PROCEDURES

Eye Contact: Irrigate immediately with water for at least 5 minutes..

Skin Contact: Wash off in flowing water or shower.

Inhaled: No adverse effects.

Swallowed : No adverse effects.anticipated by the route of exposure incidental to proper industrial handling.

SUSPECTED CANCER AGENT ?

_____ NO: This product's ingredients are not found in the lists below.

YES: _____ Federal OSHA _____ NTP _____X_____ IARC

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: N/A

LATEX CRETE # 73

_____ **VI.REACTIVITY DATA** _____

Stability: _____X_____ Stable _____ Unstable

Conditions to avoid: May coagulate if froxen at 32 F.

Incompatibility (materials to avoid): N/A

Hazardous decomposition products (including combustion products): If dried resin is burned, produces adense black smoke and noxious gases (Carbon monoxide and hydrocarbons)

Hazardous polymerization: _____ May occur _____X_____ Will not occur

Conditions to avoid: N/A

_____ **VII.SPILL,LEAK,AND DISPOSAL PROCEDURES** _____

Spill response procedure (include employee protection measures): Flash area with water immediately.Avoid unnecessary exposure and contact.

Preparing wastes for disposal (container types,neutralization,etc..) : Soak up with absorbant materials. Store in pail or drums. Bury in an approved land fill or burn solid water in an adequate incinerator.If enters sanitary sewers, flush with alarge amounts of water.

Note: Dispose of all wastes in accordance with federal,state and local regulations

VIII.SPECIAL HANDLING INFORMATION

Ventilation and engineering controls: Good general ventilation should be sufficient for most conditions.

Respiratory protection (type): Not needed for most conditions.

Eye protection (type): Use Chemical goggles or safety glasses

Gloves(specify material): Impervious gloves, vinyl or rubber.

Other clothing and equipment: Wear clean, long-sleeved, body – covering clothing.

Work practices, hygienic practices: Maintain good housekeeping standards.

Other handling and storage requirements: Should store at temperatures between 40-1000 F and use within 12 months.

Protective measures during maintenance of contaminated equipment: N/A