



**INSTALLATION OF CERAMIC TILE ON INTERNAL EXISTING FLOOR BY THICK BED METHOD**

Existing substrate	:	Kota stone/ marble/ cement mosaic tile
New tiling	:	Ceramic tile
Laticrete Adhesive proposed	:	Laticrete 226 + Laticrete 3642
Packing	:	L226- 20kg L3642 – 20 ltr
Mixing ratio	:	50kg bag L226: 1ltr L3642 + 4ltr water
Coverage	:	Approx. 12 sft for an applied thickness of 25 mm thick adhesive
Laticrete slurry bond coat proposed	:	Laticrete 111 crete filler powder+ Laticrete 3642 latex concentrate
Packing	:	L111- 20kg L3642 – 20 ltr
Mixing ratio	:	20kg bag L111: 2.5ltr L3642+5 ltr water
Coverage	:	Approx. 80-90 sft for an applied thickness of 1.5mm slurry bond coat
Laticrete grout proposed	:	
Option I	:	Laticrete tile grouts with Laticrete 1776 grout admix Plus
Packing	:	L500/600 grout powder – 10kg L1776 grout admix plus – 20 ltr
Mixing ratio	:	1 bag of 10kg of 600 series powder : 3.75 ltr of L1776 grout admix plus 1 bag of 10kg of 500 series powder : 1.75 ltr of L1776 grout admix plus
Colours available	:	43 colours
Coverage	:	Depends on the tile size, joint depth and joint width
Option II	:	Latapoxy SP100 stainfree grout
Packing	:	5.5 kg
Mixing ratio	:	Pre measured kit
Colours available	:	43 colours
Coverage	:	Depends on the tile size, joint width and depth

LTP1006/REV06/05