



MYK LATICRETE

Tile & Stone Installation Solutions

PROPOSAL FOR INSTALLATION OF CERAMIC TILE ON PLYWOOD FLOOR & WALL BY THIN SET METHOD

Existing substrate : Plywood

New tiling : Ceramic tile

Laticrete Adhesive proposed : Laticrete 290 + Laticrete 333

Packing : L290- 20kg
L333 – 20 ltr

Mixing ratio : 20kg bag L290: 6.5ltr L333

Coverage : Depends on the size of tile and thickness of adhesive applied

Tile Size	Adhesive thickness	Coverage
300x300mm	3mm	55-60 sft
450x450mm	4.5mm	35-40 sft
600x600mm	6 mm	25-30 sft
900x900mm	7.5mm	18-20 sft
> 900x900mm	9 mm	12-15 sft

Laticrete grout proposed : Option I

Laticrete tile grouts with Laticrete 1776 grout admix plus.

Packing : L500/600 grout powder – 10kg
L1776 grout admix plus – 20 ltr

Mixing ratio : 1 bag of 10kg of 600 series powder : 3.75 ltr of L1776
1 bag of 10kg of 500 series powder : 1.75 ltr of L1776

Colours available : 43 colours

Coverage : depends on the tile size, joint depth and joint width

Option II	:	Latapoxy SP100 stainfree grout
Packing	:	5.5 kg
Mixing ratio	:	Pre measured kit
Colours available	:	43 colours
Coverage	:	Depends on the tile size, joint width and depth