



**PROPOSAL FOR INSTALLATION OF VITRIFIED TILE ON INTERNAL & EXTERNAL FLOOR
BY INTERNAL & EXTERNAL FLOOR BY**

Existing substrate : Concrete

New tiling : Vitrified tile

Laticrete Adhesive proposed : Laticrete 226 + Laticrete 3642

Packing : L226- 20kg
L3642 – 20 ltr

Mixing ratio : 50kg bag L226: 1ltr L3642 + 4ltr water
Coverage : Approx. 12 sft for an applied thickness of 25
mm thick adhesive

**Laticrete slurry bond coat proposed :Laticrete 111 crete filler powder+ Laticrete 3642
latex concentrate**

Packing : L111- 20kg
L3642 – 20 ltr

Mixing ratio : 20kg bag L111: 2.5ltr L3642+5 ltr water

Coverage : Approx. 80-90 sft for an applied thickness of
1.5mm slurry bond coat

Laticrete grout proposed :

Option I : Laticrete tile grout with Laticrete grout admix

Packing : L500/600 grout powder – 10kg
L grout admix – 20 ltr

Mixing ratio : 1 bag of 10kg of 600 series powder : 3.75 ltr of L
1 bag of 10kg of 500 series powder : 1.75 ltr of L

Colours available : 43 colours

Coverage : Depends on the tile size, joint depth and joint width

Option II	:	Latapoxy SP100 stainfree grout
Packing	:	5.5 kg
Mixing ratio	:	Pre measured kit
Colours available	:	43 colours
Coverage	:	Depends on the tile size, joint width and depth