



PROPOSAL FOR INSTALLATION OF GLASS MOSAIC TILE ON METAL FLOOR BY THIN SET METHOD

Existing substrate : Metal (Steel, Aluminium)

New tiling : Glass mosaic tile

Laticrete Adhesive proposed : Laticrete Latapoxy 210 epoxy adhesive

Packing : 16 kg

Coverage : Depends on the size of tile and thickness of adhesive applied

Tile Size	Adhesive thickness	Coverage
300x300mm	3mm	55-60 sft
450x450mm	4.5mm	35-40 sft
600x600mm	6 mm	25-30 sft
900x900mm	7.5mm	18-20 sft
> 900x900mm	9 mm	12-15 sft

Laticrete grout proposed : Option I

Laticrete tile grouts with Laticrete 1776 grout admix plus.

Packing : L500/600 grout powder – 10kg
L1776 grout admix plus – 20 ltr

Mixing ratio 1 bag of 10kg of 600 series powder : 3.75 ltr of L1776 grout admix plus
1 bag of 10kg of 500 series powder : 1.75 ltr of L1776 grout admix plus

Colours available : 43 colours

Coverage : Depends on the tile size, joint depth and joint width

Option II **Latapoxy SP100 stainfree grout**

Packing : 5.5 kg

Mixing ratio : Pre measured kit

Colours available : 43 colours
Coverage : Depends on the tile size, joint width and depth