



MYK LATICRETE

Tile & Stone Installation Solutions

PROPOSAL FOR INSTALLATION OF NATURAL STONE ON INTERNAL EXISTING FLOOR BY THICK BED METHOD

Existing substrate : Kota stone/ marble/ cement mosaic tile

New tiling : Natural Stone

Laticrete Adhesive proposed : Laticrete 226 + Laticrete 3642

Packing : L226- 20kg
L3642 – 20 ltr

Mixing ratio : 50kg bag L226: 1ltr L3642 + 4ltr water
Coverage : Approx. 12 sft for an applied thickness of 25 mm thick adhesive

Laticrete slurry bond coat proposed Laticrete 111 crete filler powder+ Laticrete 3642 latex concentrate

Packing : L111- 20kg
L3642 – 20 ltr

Mixing ratio : 20kg bag L111: 2.5ltr L3642+5ltr water

Coverage : Approx. 80-90 sft for an applied thickness of 1.5mm slurry bond coat

**Laticrete grout proposed :
Option I : Laticrete tile grout with Laticrete 1776 grout admix Plus**

Packing : L500/600 grout powder – 10kg
L1776 grout admix plus – 20 ltr

Mixing ratio : 1 bag of 10kg of 600 series powder : 3.75 ltr of L1776 grout admix plus
1 bag of 10kg of 500 series powder : 1.75 ltr of L1776 grout admix plus

Colours available : 43 colours

Coverage : Depends on the tile size, joint depth and joint width

Option II	:	Latapoxy SP100 stainfree grout
Packing	:	5.5 kg
Mixing ratio	:	Pre measured kit
Colours available	:	43 colours
Coverage	:	Depends on the tile size, joint width and depth