



## INSTALLATION OF NATURAL STONE ON METAL WALL BY THIN SET METHOD

Existing substrate	:	Metal (Steel, Aluminium)
New tiling	:	Natural Stone
Laticrete Adhesive proposed	:	Laticrete Latapoxy 300 epoxy adhesive
Packing	:	5.5 kg
Coverage	:	Depends on the size of tile and thickness of adhesive applied

Tile Size	Adhesive thickness	Coverage
300x300mm	3mm	55-60 sft
450x450mm	4.5mm	35-40 sft
600x600mm	6 mm	25-30 sft
900x900mm	7.5mm	18-20 sft
> 900x900mm	9 mm	12-15 sft

Laticrete grout proposed	:	
Option I	:	Laticrete tile grouts with Laticrete 282 grout admix
Packing	:	L500/600 grout powder – 10kg L282 grout admix – 20 ltr
Mixing ratio	:	1 bag of 10kg of 600 series powder : 3.75 ltr of L282
	:	1 bag of 10kg of 500 series powder : 1.75 ltr of L282
Colours available	:	43 colours
Coverage	:	Depends on the tile size, joint depth and joint width
Option II	:	Latapoxy SP100 stainfree grout
Packing	:	5.5 kg
Mixing ratio	:	Pre measured kit
Colours available	:	43 colours
Coverage	:	Depends on the tile size, joint width and depth