



# Grout Colours



## MYK LATICRETE

Pick your favourite colour from MYK LATICRETE Range of Grouts



## MYK LATICRETE

Tile & Stone Installation Solutions

**LATAPOXY SP-100 Stainfree Grout For Floor N' Walls-700 Series** is a 100% solid epoxy grout that is stainfree, colour-fast and chemical resistant for use with ceramic & vitrified tiles, marble and stone.

**LATAPOXY 2000 Industrial Epoxy Grout** is a highly chemical resistant epoxy grout formulated for use with ceramic tile, pavers, floor brick, packing tile and stone.

**COVERAGE :**

Approximate sq. ft. coverage per # 1 unit of SP-100. Double for # 2 unit.

TILE SIZE X THICKNESS	JOINT WIDTH						
	2mm	3mm	4mm	6mm	8mm	10mm	12mm
in mm							
100x 100x 3	291	195	147	99	75	61	51
150x 150x 4	326	218	164	110	83	67	56
200x 150x 5	296	199	150	100	76	61	51
200x 200x 5	348	232	175	117	88	71	59
200x 300x 6	347	232	174	117	88	71	59
300x 300x 6	434	290	218	146	110	88	74
400x 400x 6	578	386	290	194	146	117	98
450x 450x 7	557	372	279	187	140	112	94
500x 500x 8	542	362	271	181	136	109	91
600x 600x 8	650	434	325	217	163	131	109

**Approximate sq. ft. coverage for Glass Mosaic**

TILE SIZE	JOINT WIDTH	JOINT DEPTH
20mm x 20 mm	1.5 mm	2 mm

600 Series Unsanded Grout- 125 Sq. ft. to 130 Sq. ft. per 10 kg. bag

500 Series Sanded Grout- 150 Sq. ft. to 175 Sq. ft. per 10 kg. bag

SP-100- 70 Sq. ft. to 80 Sq. ft. per # 1 Unit

- Quantities shown are approximate and are given for estimating purposes only. Actual job site coverages may vary. **NOTE:** It is always good practice when calculating coverage to allow for 10 - 15% additional material for wastage and spillage.

**Corporate Office:** MYK LATICRETE INDIA PVT. LTD. (Formerly LATICRETE® INDIA PVT. LTD.,) 6-3-569 / 2, First Floor, Kamadhenu Complex, Rockdale Compound, Somajiguda, Hyderabad 500 082. (A.P) India. Tel: +91-40-30413100 (30 lines). Fax: +91-40-23378784. **E-mail:** contact@myklaticrete.com **www.myklaticrete.com**

**Regional Offices:** Bengaluru: 080-23134495 | Bhubaneswar: 0674-326 3100 | Chennai: 044-2811 2904 | Jaipur: 0141-2210 079 | Kochi: 0484-4027199 | Kolkata: 033-2465 6443 | Ludhiana: 0161-250 3686 | Mumbai: 022-3268 8795 | New Delhi: 011-2637 1584 | Pune: 020-3253 5985

Available at:

DS-9-REV-02/08

verbcommunications.net

An MYK GROUP enterprise

LATICRETE, LATAPOXY and the logo are Registered Trademarks of LATICRETE International, Inc.



## MYK LATICRETE

Tile & Stone Installation Solutions

# Grout Colour Selector

**LATICRETE Unsanded Grout - 600 Series** is designed for use with LATICRETE 1776 Grout Admix plus for joint width 1mm to 6mm for porous & absorbent type tiles, non-vitreous clay tiles, marble & glazed wall tiles.

**COVERAGE:**

Approximate sq. ft. coverage per 10kg. bag.

TILE SIZE X THICKNESS	JOINT WIDTH					
	1mm	2mm	3mm	4mm	5mm	6mm
in mm						
100x100x3	1430	720	480	335	270	225
150x150x4	1610	810	540	375	301	252
200x150x5	1470	740	490	342	274	229
200x200x6	1720	860	570	332	266	267
200x300x6	1720	860	570	399	319	266
300x300x6	2150	1070	710	496	398	332
400x400x6	2860	1430	950	661	529	442
450x450x7	2760	1380	920	637	510	425
500x500x8	2680	1340	890	619	496	413
600x600x8	3210	1610	1070	737	594	496

**LATICRETE Sanded Grout - 500 Series** is designed to be used with LATICRETE 1776 Grout Admix plus for joint width 3mm to 12mm for non-absorbent and vitrified type tiles.

**COVERAGE:**

Approximate sqft coverage per 10kg. bag.

TILE SIZE X THICKNESS	JOINT WIDTH			
	6mm	8mm	10mm	12mm
in mm				
100x 100x 3	225	171	138	116
150x 150x 4	252	190	153	128
200x 150x 5	229	173	139	116
200x 200x 5	267	201	161	135
200x 300x 6	266	200	161	134
300x 300x 6	332	249	200	168
400x 400x 6	442	332	266	222
450x 450x 7	425	320	256	214
500x 500x 8	413	310	249	208
600x 600x 8	496	372	298	249

**RECOMMENDED FOR:**

- CERAMIC FLOOR & WALL TILE
- QUARRY TILE
- MARBLE
- MOSAIC
- STONE
- PORCELAIN TILE
- FLOOR BRICK
- PAVERS
- SLATE

**ADVANTAGES:**

- COLOUR-FAST
- WEATHER RESISTANT
- EASY MAINTENANCE
- NON-SHRINKING
- NON-CRACKING
- EASY APPLICATION AND CLEAN UP



# LATICRETE® and LATAPOXY® GROUTS

<b>44 Bright White</b> CLASSIC Group I	
<b>03 Silk</b> CLASSIC Group I	
<b>85 Almond</b> CLASSIC Group I	
<b>23 Antique White</b> CLASSIC Group I	
<b>18 Sauterne</b> CLASSIC Group I	
<b>54 Dusty Rose</b> CLASSIC Group I	
<b>05 Sierra Sunrise</b> DESIGNER Group II	
<b>51 Buff</b> CLASSIC Group I	
<b>92 Saltillo</b> DESIGNER Group II	
<b>07 Canyon Red</b> DESIGNER Group II	
<b>06 Mayan Red</b> DESIGNER Group II	
<b>46 Quarry Red</b> CLASSIC Group I	
<b>04 Sable</b> DESIGNER Group II	
<b>17 Marble Beige</b> CLASSIC Group I	
<b>27 Hemp</b> DESIGNER Group II	
<b>34 Sandstone</b> CLASSIC Group I	
<b>61 Parchment</b> CLASSIC Group I	
<b>35 Mocha</b> CLASSIC Group I	
<b>11 Inca Gold</b> DESIGNER Group II	
<b>13 Lichen</b> DESIGNER Group II	
<b>15 Sage</b> DESIGNER Group II	
<b>25 Ivy</b> DESIGNER Group II	
<b>88 Silver Shadow</b> CLASSIC Group I	
<b>89 Smoke Grey</b> DESIGNER Group II	
<b>91 Slate Grey</b> CLASSIC Group I	
<b>24 Natural Grey</b> CLASSIC Group I	
<b>78 Sterling Silver</b> CLASSIC Group I	
<b>42 Platinum</b> CLASSIC Group I	
<b>45 Raven</b> CLASSIC Group I	
<b>22 Midnight Black</b> CLASSIC Group I	
<b>102 Aqua Blue</b> DESIGNER Group II	
<b>101 Sky Blue</b> CLASSIC Group I	
<b>103 Sapphire</b> DESIGNER Group II	
<b>108 Alpine Blue</b> CLASSIC Group I	
<b>109 Burgundy</b> CLASSIC Group I	
<b>110 Light Green</b> CLASSIC Group I	

Grout shades are approximate guides only. Actual shade and texture will depend on jobsite conditions. Shades shown have been developed using LATICRETE Grout Admix 1776. Verify actual appearance and compatibility with a test area before installation commences. If using more than one batch, blend grout with different batch numbers.