



## LATICRETE® 190 SEALER Grout and Stone Protector



### PRODUCT DESCRIPTION

LATICRETE® 190 Sealer is a invisible, penetrating sealer that protects against stains, Soiling, discoloration and efflorescence. It is a clear, non-flammable solution which cures to an invisible water repellent coating. Applied on marble, brick, limestone and mortar joints it will seal and reduce staining and water absorption. Will not change the color of the stone or ceramic tile.

### Application

- Interior and exterior sealer to protect installations against soil and stains.
- Seals mortar and stucco
- Ideal to protect against efflorescence.
- Can be used as a grout release by treating ceramic tile prior to the application of grout.
- Weather and soil protection on stone and brick facades and walls.

### Advantages

- Weather resistant - protects stone, brick and tile
- Easy to apply – no special tools required
- Water base – non-flammable

### Packaging

5ltr can  
20 ltr pail

### Coverage

1Liter covers approximately 75 sft depending on the porosity of the surface.

### Shelf Life

Minimum One (1) year when protected from freezing

### Limitations

- Do not apply when surface or temperature is below 45°-85°F(7°-30° C)

### Cautions

- LATICRETE 190 Sealer is strongly alkaline. Protective gloves and eye protection should be worn when using the product. When spraying avoid inhaling the vapors of mist. Do not take internally
- Keep out of reach of children.
- Protect Aluminum and glass surface from direct prolonged exposure to liquid or spray.
- Wear rubber gloves when applying with sponge

### INSTALLATION

#### Preparation

The surface to be sealed must be clean and dry. Surface temperature should be between 45°-85°F (7-30° C). Allow cements, stucco and mortars to cure 24 hours before applying sealer. Test on a small unobtrusive area before coating entire surface.

#### Application

Apply the sealer with a sponge, brush or sprayer. Allow to penetrate 5 to 10 minutes. Wipe Off excess sealers. Allow LATICRETE 190 Sealer to cure for 24 hours. One application is sufficient for most installations.

NOTE: Excess material should be wiped from the surface of marble, granite, glazed tile or rock when applied on horizontal surfaces. A white residue may occur if excess material is allowed to dry on a polished surface.

**Cleaning** – LATICRETE 190 Sealer cleans easily with fresh water immediately after use. Do not allow dried residue remain on polished surface, glass or aluminum.

### AVAILABILITY AND COST

#### Availability

LATICRETE and LATAPOXY materials are available worldwide. For distributor information:  
Telephone: +91-40-30413100

FAX: +91-40-23378784  
e-mail: [contact@myklaticrete.com](mailto:contact@myklaticrete.com)

### **Cost**

Contact a LATICRETE Distributor in your area.

### **WARRANTY:**

MYK LATICRETE India Pvt Ltd warrants that LATICRETE® 190 sealer is free from manufacturing defects and will not break down, deteriorate or disintegrate under normal usage for a period of one (1) year from date of purchase subject to the terms and conditions stated in LATICRETE Product Warranty

### **MAINTENANCE**

LATICRETE and LATAPOXY materials are premium quality construction products requiring no maintenance to ensure performance.

### **TECHNICAL SERVICES**

#### ***Technical assistance***

Information is available by calling the LATICRETE Technical Service

Telephone: +91-40-30413100

FAX: +91-40-23378784

e-mail: [contact@myklaticrete.com](mailto:contact@myklaticrete.com)

#### **MYK Laticrete India Pvt Ltd.**

6-3-569/2, First Floor, Kamadhenu Complex

Rockdale Compound, Somajiguda

Hyderabad – 500082 (A.P)

Tel: +91-40-30413100

Fax: +91-40-23378784

e-mail: [contact@myklaticrete.com](mailto:contact@myklaticrete.com)

Website: [www.myklaticrete.com](http://www.myklaticrete.com)

