



1766 Liquid Admix, Latex Thinset Mortar Additive 4237, 4230,4325, 3810,3811,3812,4237  
Rapid,5150 Rapid.

---

#### IV.FIRE AND EXPLOSION

---

Flash Point, F (give method): Not flammable or combustible in liquid form

Auto ignition temperature,F: N/A

Flammable limits in air, volume % : N/A      Lower (LEL)\_\_\_\_\_ Upper (UEL)

Fire extinguishing materials:

\_\_\_\_\_ water spray

\_\_\_\_\_ carbon dioxide

\_\_\_\_\_ other:

\_\_\_\_\_ foam

\_\_\_\_\_ dry chemical

Special fire fighting procedures: N/A

Unusual fire and explosion hazards: N/A

---

#### V.HEALTH HAZARD INFORMATION

---

SYMPTOMS OF OVEREXPOSURE for each potential route of exposure.

Inhaled: No adverse effects are anticipated from inhalation.

Contact with skin or eyes: Short exposure not likely to cause significant skin irritation. Eye contact  
May cause slight,temporary eye irritation.

Absorbed through skin: Skin absorption is unlikely due to physical properties

Swallowed: Single dose oral toxicity is believed to be low.No hazards anticipated from ingestion  
Incidental to industrial exposure.

---

**HEALTH EFFECTS OR RISKS FROM EXPOSURE.** Ezplain in lay terms . Attach extra page if  
more space is needed:

Acute: N/A

Chronic: N/A

---

#### FIRST AID: EMERGENCY PROCEDURES

Eye Contact: Irrigate immediately with water for at least 5 minutes.

Skin Contact: Wash off in flowing water or shower.

Inhaled : No adverse effects

Swallowed:No adverse effects anticipated by this route of exposure incidental to proper  
industrial  
Handling.

---

SUSPECTED CANCER AGENT ?

\_\_\_\_\_ NO: This product's ingredients are not found in the lists below.

YES: \_\_\_\_\_ Federal OSHA \_\_\_\_\_ NTP \_\_\_\_\_ IARC

---

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: N/A

1766 Liquid Admix, Latex Thinset Mortar Additive 4237,4230,4235,3810,3811,3812,4237  
Rapid,  
5150 Rapid

\_\_\_\_\_ **VI.REACTIVITY DATA** \_\_\_\_\_

Stability: \_\_\_\_\_X\_\_\_\_\_ Stable \_\_\_\_\_ Unstable

Conditions to avoid: May coagulated if frozen at 32 F

Incompatibility (materials to avoid): N/A

Hazardous decomposition products (including combustion products ): If dried resin is burned,  
produces  
A dense black smoke and noxious gases (Carbon monoxide and hydrocarbons).

Hazardous polymerization: \_\_\_\_\_ May occur \_\_\_\_\_X\_\_\_\_\_ Will not occur

Conditions to avoid: N/A.

\_\_\_\_\_ **VII.SPILL,LEAK, AND DISPOSAL PROCEDURES** \_\_\_\_\_

Spill response procedures (include employee protection measures): Flush area with water  
immediately.

Avoid unnecessary exposure and contact.

Preparing wastes for disposal (container types, neutralization , etc.): Soak up with absorbent  
materials.

Store in pails or drums. Bury in an approved landfill or burn solid wastes in an adequate incinerator.  
If enters sanitary sewers, flush with large amounts of water.

NOTE: Dispose of all wastes in accordance with federal, state and local regulations.

\_\_\_\_\_ **VIII.SPECIAL HANDLING INFORMATION** \_\_\_\_\_

Ventilation and engineering controls: Good general ventilation should be sufficient for most  
conditions

Respiratory protection (type): No respiratory protection should be needed if good ventilation is maintained.

Eye protection (type): Use Chemical goggles or safety glasses

Gloves(specify material): Impervious gloves, vinyl or rubber

Other clothing and equipment:Wear clean, long – sleeved, body – covering clothing..

Work practices, hygienic practices: Maintain good housekeeping standards

Other handling and storage requirements: Should Store at temperatures between 40- 100F and Used within 12 Months.

Protective measures during maintenance of contaminated equipment: Impervious gloves ,vinyl Or rubber, safety glasses, wear clean, long – sleeved, body – covering clothing.