

MYK LATICRETE Product Recommendation Chart

Application Wise

Area of Application	Product
Surface Preparation	
Floor-Thick Mortar Bed	L 3642/ L 226
Tile / Stone Fixing	
Internal Floor	L 290
Internal Wall	L 290
Tile over Tile	L 254/L 111 + L 73/L 4237
Tile/stone over Gypsum board	L 254/L 111 + L 73/L 4237
Tile/stone over Plywood	L 254/L 290 + L 333
Tile/stone over Steel/ Metal	L 210 / L 300
Tile/stone over External wall	L 254/L 111 + L 73/L 4237
Glass Mosaic Tile over Floor / Wall	L 254/L 252
Grouting	
Internal floor like Hall, Bedroom, Office etc.	L 500 / L 600 + L 1776
Commercial Internal floor like Office rooms, Meeting rooms etc.	L 500 / L 600 + L 1776
Commercial Internal floor like Corridor, Lobby, Service area etc.	L SP-100/Dazzle™ Grout
Residential / Commercial kitchen / Toilet	L SP-100/Dazzle™ Grout
Swimming pool / Water bodies	L SP-100/Dazzle™ Grout
Industrial floor	L 2000
External wall	L 500 / L 600 + L 1776
Waterproofing	
Bathroom	L 9237 + Corner Fabric
Terrace	L 9237 + Corner Fabric
Swimming pool	L 9235
External wall	L 9237
Wall Putty	

Note: Above is a general recommendation chart. For proper product selection & application, refer to LATICRETE® product data sheet or contact MYK LATICRETE technical service department.