



## **CLENZA EF**

### PRODUCT DESCRIPTION:

CLEANZA EF is an acidic cleaner which can be used to remove efflorescence from tile and stone surfaces and grout joints. CLENZA EF is water soluble and can be used in both interior and exterior applications.

### AREAS OF APPLICATION:

- Ceramic Tile
- Vitrified Tile
- Natural Stone
- Concrete
- Quarry Tile
- Cement Grout Joints

### ADVANTAGES:

- Fast acting
- Easy to Use
- Low Odour

### PACKAGING:

1 litre, 5 litres and 20 litres.

### COVERAGE:

15 to 50 sq.foot per litre depending upon the porosity of the substrate

### CAUTIONS:

Clenza EF is acidic in nature and caution should be maintained while handling the product. It should not be used on acid sensitive and polished stone. Store in cool place away from heat and fire. Avoid contact with skin and eyes. Do not inhale and use it in open ventilated areas. Do not swallow and wear gloves during application.

### APPLICATION:

- 1) Pour the contents in a plastic container.
- 2) Apply over stained area and scrub with medium hard brush. Let it stay for 3-5 minutes and keep scrubbing periodically.
- 3) Do not allow Clenza EF to dry on the surface. After application procedure, neutralize the area washing with clean potable water.

### TECHNICAL DATA:

Appearance:	Clear Liquid
Specific gravity:	1.05 – 1.10
pH:	7 - 9

### AVAILABILITY:

MYK LATICRETE Materials-  
For distributor information contact  
Telephone: +91-40-30413100  
Fax: +91-40-23378784  
Email: [contact@myklaticrete.com](mailto:contact@myklaticrete.com)

### STORAGE:

After usage, close the container well sealed to avoid contamination and damages. Store in original container only. Store and use between temperature 4<sup>o</sup> C and 40<sup>o</sup> C

### WARRANTY:

MYK Laticrete India Private Limited warrants to the original customer that CLEANZA EF is free from manufacturing defect and will not deteriorate or disintegrate under normal usage for a period of 1 year from the date of purchase subject to the terms and conditions stated in MYK Laticrete product warranty.

### TECHNICAL SUPPORT: Information

is available by contacting MYK  
Laticrete Technical service  
Telephone: +91-40-30413100 Fax:  
+91-40-23378784  
Email: [contact@myklaticrete.com](mailto:contact@myklaticrete.com)

MYK LATICRETE INDIA PVT LTD 8-2-703/A,  
Fourth Floor, Leela Gopal Towers, Road No.  
12, Banjara Hills, HYDERABAD – 500 034,  
INDIA [www.myklaticrete.com](http://www.myklaticrete.com)